

## BRIGHTO SUPER TEXTURE

<b>General Description</b>	<b>Brighto Super Texture</b> is a high quality acrylic based waterborne texture paint which is used to produce different kinds of textural effects for interior/exterior masonry surfaces such as brickwork, plaster and concrete. It can be over coated with a wide range of colors, which gives pleasing effects.	
<b>Pack Size</b>	6 Kg and 24 Kg	
<b>Colour Range</b>	White Only	
<b>Film Properties</b> <b>Water Resistance</b>	Resistant to the levels of atmospheric humidity present in normal environment.	
<b>Composition (Nominal)</b>	Pigment: Inert Filler Binder: Acrylic Copolymer Solvent: Water	
<b>Volume Solids</b>	49 ± 2% (nominal)	
<b>Density</b>	1.70 ± 0.03 Theoretical	
<b>Non-volatile Matter Content</b>	70 ± 2; Theoretical	
<b>VOC Contents</b>	0.001 g / L; ASTM D 3960	
<b>Film Thickness/Coat</b>	Wet: 200 - 250 Micrometers Dry: 98 - 122 Micrometers	
<b>Drying Times</b>	Depends on temperature, humidity, air movements and film thickness	
<b>Touch Dry</b> <b>Recoat</b>	2 - 4 Hours 4 - 8 Hours	
<b>Theoretical Coverage</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 4 - 5 m <sup>2</sup> /liter /coat.	
<b>Application</b>	Texture Roller, Design Roller	
<b>Thinner</b>	Water	
<b>Dilution</b>	Maximum 5% (If Required)	
<b>Conventional Spray</b>	Not Applicable	
<b>Cleaning Up</b>	Clean all equipment with clean water immediately after use.	
<b>Surface Preparation</b>	New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of paris or white cement. Allow to dry. Rub down the surface with abrasive paper. Apply <b>Brighto Interior Primer</b> and allow to dry. Apply <b>Brighto Interior Filler</b> and allow to dry. Apply <b>Brighto Aroma Matt Enamel</b> and allow to dry. For exterior surfaces, Apply <b>Brighto Exterior Primer</b> and allow to dry. Apply <b>Brighto Exterior Filler</b> and allow to dry. Apply <b>Brighto Aroma Matt Enamel</b> and allow to dry. Now the surface will be smooth and ready for <b>Brighto Super Texture</b> to be applied.	
<b>Recommended Paint System</b>	Brighto Interior Primer / Exterior Primer	1 Coat
	Brighto Interior Filler / Exterior Filler	2 Coats
	Brighto Aroma Matt Enamel	1 - 2 Coats
	Brighto Super Texture	1 Thick Coat
<b>Flash Point</b>	36°C	
<b>Safety, Health and Environmental Information</b>	Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.	

*Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.*